



ALL WEATHER PVC CEMENT

Learn more



All Weather PVC cement uses an ultra low VOC, medium bodied formula that sets fast and bonds with high strength in adverse weather conditions for non-pressure rigid and flexible PVC electrical duct and conduit applications, including Schedule 40 and Schedule 80. It's suitable for tight tolerance joints through 8 inch (200 mm) diameter, making it a versatile choice for a wide range of electrical conduit installations where reliable, durable solvent welds are required. NSF certified, meets ASTM D2564, CSA C22.2 No. 211.1 and No. 211.2. NSF for pw/dwv/sw and Uniform Plumbing Code. Suitable for UL-651 & NEMA TC-2, TC-6 & TC-8.

Features and Benefits

- Extremely fast set time
- Low VOC for reduced fumes
- All rigid and flexible PVC conduit & non-pressure pipe compatibility

CLEAR

Part#	UPC	Description	Size (oz)	Standard	Master
PV16AWCL	86460	Clear Medium Bodied All Weather PVC Cement (Pint)	16	1	12
PV32AWCL	86461	Clear Medium Bodied All Weather PVC Cement (Quart)	32	1	12
PV128AWCL	86462	Clear Medium Bodied All Weather PVC Cement (Gallon)	128	1	6

ACCESSORIES

Part#	UPC	Description	Standard	Master
PVQ	86487	Empty Can (Quart)	1	12
PVD50P	86488	Replacement Pint Dauber (1/2" to 1-1/4" Pipe)	50	
PVD50Q	86489	Replacement Quart Dauber (1/2" to 1-1/4" Pipe)	50	
PVD150P	86490	Replacement Pint Dauber (1-1/2" to 3" Pipe)	50	
PVD150Q	86491	Replacement Quart Dauber (1-1/2" to 3" Pipe)	50	