



NO MARK

GRADE MARK

| THREAD DATA | | |
|--|--|--|
| Size: #10 | Threads per in.: 32 | Series Designation: UNF |
| Thread Class or Type: 2B | Pitch and Functional Dia.: 0.1736 - 0.1697 | Minor Dia Max/Min.: 0.1640 - 0.1560 |
| Tensile Stress Area: 0.0200 | Standard: ASME B1.1 - 2003 (R2008) | |
| DIMENSIONAL DATA | | |
| FILTER - Thread Class or Type: 2B | Type: Hex Machine Screw Nuts | Standard: ASME B18.2.2-2015 |
| Size: #10 | Nominal: 0.19 | F - Width Across Flats: 0.375 - 0.362 |
| G - Width Across Corners: 0.433 - 0.413 | H - Thickness: 0.130 - 0.117 | Max Runnout of Bearing Surface w/Thread PD, FIM: 0.013 |
| PHYSICAL REQUIREMENTS | | |
| Nominal: 0.19 | Type: Hex Machine Screw Nuts | Grade: ASME B18.2.2 - 2010, Brass |
| Typical Material: Brass (UNS C2600/C27000) | | |
| FINISH DATA | | |
| Finish: As received steel | K factor (ref. DIN 946): 0.2 | |

