


# Hex



## F 467B

### GRADE MARK

THREAD DATA		
Size: 5/16	Threads per in.: 18	Series Designation: UNC
Thread Class or Type: 2B	Pitch and Functional Dia.: 0.2817 - 0.2764	Minor Dia Max/Min.: 0.2650 - 0.2520
Tensile Stress Area: 0.0524	Standard: ASME B1.1 - 2003 (R2008)	
DIMENSIONAL DATA		
FILTER - Thread Class or Type: 2B	Type: Hex	Standard: ASME B18.2.2-2015
Size: 5/16	Nominal: 0.313	F - Width Across Flats: 0.500 - 0.489
G - Width Across Corners: 0.577 - 0.557	H - Thickness: 0.273 - 0.258	Runout of Bearing Surface, FIM Proof Stress Up to 150,000 psi: 0.016 Max
Runout of Bearing Surface Proof Stress 150,000 psi and Greater: 0.011 Max		
PHYSICAL REQUIREMENTS		
Nominal: 0.312	Type: Hex	Grade: ASTM F467-2013e2, Brass
Typical Material: Cu 270	Hardness: HRF 55 min.	Proof Stress, psi.: 60000
Proof Load, lbs.: 3,144		
FINISH DATA		
Finish: As received steel	K factor (ref. DIN 946): 0.2	

