


Hex Lag Screw



THREAD DATA		
Size: 5/16	Threads per in.: 9	Thread Class or Type: Lag
Major Diameter: 0.324 - 0.298	Minor Dia Max/Min.: 0.228 - 0.210	Standard: ASME B18.2.1-2012
DIMENSIONAL DATA		
Type: Hex Lag Screw	Standard: ASME B18.2.1-2012	Nominal Diameter: 0.313
E - Body Diameter : 0.324 - 0.298	F - Width Across Flats: 0.500 - 0.484	G - Width Across Corners: 0.577 - 0.552
R - Fillet Radius: 0.030 - 0.010	H - Head Height: 0.235 - 0.195	L _T - Thread Length for Screw Length 6 in. or less: Lesser of .5L+0.5" or 6"
Point Type: Gimlet	L - Length: 5	Length Tolerance: ±0.12
PHYSICAL REQUIREMENTS		
Nominal: 0.313	Standard: ASTM A307-2014e1	Typical Materials: carbon steel: 1006 - 1022
Hardness: HRB 69 - 100	Tensile Load, Min. (lbf): 2639 ref. (min. minor dia X 60 ksi)	Calculated Shear Load-BODY (ref.)(lbf): 1583
Calculated Shear Load-THREADS (ref.)(lbf): 1319	Straightness Factor: 0.03	
FINISH DATA		
Finish: Zinc & Clear, non-hexavalent/Cr(VI) free - .0001"/ 3µm	K factor (ref. DIN 946): 0.22	Standard: ASTM F1941/F1941M-2016, Fe/Zn 3AN

² Calculated Pretension is equal to 75% of the bolt's yield strength achieved when using the indicated Tightening Torque.

