



Hex Tap Bolts



F 468K

GRADE MARK

THREAD DATA		
Size: 5/16	Threads per in.: 18	Series Designation: UNC
Thread Class or Type: 2A	Major Diameter: 0.3113 - 0.3026	Pitch and Functional Dia.: 0.2752 - 0.2712
Tensile Stress Area: 0.0524	Standard: ASME B1.1 - 2003 (R2008)	
DIMENSIONAL DATA		
Type: Hex Tap Bolts	Standard: IFI - 199	Nominal Diameter: 0.313
F - Width Across Flats: 0.500 - 0.484	G - Width Across Corners: 0.577 - 0.552	R - Fillet Radius: 0.030 - 0.010
H - Head Height: 0.235 - 0.195	L _T - Thread Length for Screw Length 6 in. or less: Fully Threaded	Point Type: Non-pointed
L - Length: 1-1/4	Length Tolerance: +0.02/-0.04	
PHYSICAL REQUIREMENTS		
Nominal: 0.313	Standard: ASTM F468-2013, Silicon Bronze	Typical Materials: Cu 651
Hardness: HRB 95 - 75	Tensile Load, Min. (lbf): 3668	Yield PSI, 2% Offset, Machined Specimen: 55,000
Tensile Strength, Min. (psi): 70,000	Tensile Strength, Max. (psi): 100,000	Calculated Shear Load-BODY (ref.)(lbf): 2,201
Calculated Shear Load-THREADS (ref.)(lbf): 1,834	Straightness Factor: N/A	Calculated Pretension ² (lbf) : 2,162
Tightening Torque ¹ : 11 ft.lbf, 135 in.lbf, 15.3 Nm		
FINISH DATA		
Finish: As received steel	K factor (ref. DIN 946): 0.2	

¹ These torque values are based on K factors determined using DIN 946, tightening tension of 75% of the yield strength, and the calculation formula T=KDP. These values are advisory only. The torque for assembling critical joints should be determined and/or verified through actual experimentation by the user. The IFI is not responsible for any losses or claims resulting from the use of these values. ² Calculated Pretension is equal to 75% of the bolt's yield strength achieved when using the indicated Tightening Torque.

