

PRODUCT SPECIFICATIONS



Product Image



Polyester Pull Line Measuring Tape

Polyester pull line is a pre-lubricated, lightweight, and abrasion resistant pulling line that is manufactured using a proprietary process designed for high temperature and high tensile strength cable pulling applications. It is printed with easy to read sequential footage markings and is manufactured to provide a low coefficient of friction to help minimize duct melting. It easily pulls and installs wire and fiber optic cables within PVC and HDPE ducts.

Features:

- Polyester
- Pre-lubed
- Abrasion resistant
- Sequentially marked
- Low elongation for safer handling

Product Dimensions

PN#	Weight	Length	Min. Breaking Strength
1/2"			
DWP500Z	4.00+/-3%	500 ft	1250 LBF
DWP1500Z	12.00+/-3%	1500 ft	1250 LBF
DWP3000Z	23.00+/-3%	3000 ft	1250 LBF
5/8"			
DWP501Z	6.00+/-3%	500 ft	1800 LBF
DWP1501Z	17.00+/-3%	1500 ft	1800 LBF
DWP3001Z	34.00+/-3%	3000 ft	1800 LBF
3/4"			
DWP502z	8.00+/-3%	500 ft	2500 LBF
DWP1502Z	24.00+/-3%	1500 ft	2500 LBF
DWP3002Z	48.00+/-3%	3000 ft	2500 LBF
* Made in Vietnam			