

Positioning Devices

COMPANY

L H DOTTIE CO

6131 GARFIELD AVE
 COMMERCE, CA 90040-3610 United States

E478898

Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type	Bundle Dia.		Loop Tensile Str. N	Operating Temp. °C		Min. Install. Temp. °C	Resistant to UV Light	Air Handling Spaces	IEC 62275 Type
		mm			Min	Max				
		Min	Max		Min	Max				
Nonmetallic Cable Ties - Nylon										
DT48H	2,21	7	365	778	-40	85	-20	-	AH-2	-
DT48HB	2,21	7	365	778	-40	85	-20	Y	AH-2	-
GT-1220HD	2,21	7	365	778	-40	85	-20	-	AH-2	-
GT-1220HDUV	2,21	7	365	778	-40	85	-20	Y	AH-2	-

Nonmetallic Cable Ties - Nylon Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Dia.		Loop Tensile Str. N	Operating Temp. °C		Min. Install. Temp. °C	Resistant to UV Light	Plenum Rating	Also Classified to [^] IEC 62275 and EN 62275
		mm			Min	Max				
		Min	Max		Min	Max				
DT11	2S,21S	3	70	222	-40	85	-20	-	AH-2	-
DT11B(b)	2S,21S	3	70	222	-40	85	-20	Y	AH-2	-
DT11BBULK	2,21	3	70	222	-40	85	-20	Y	AH-2	-
DT11BULK	2,21	3	70	222	-40	85	-20	-	AH-2	-
DT14	2S,21S	3	102	222	-40	85	-20	-	AH-2	-
DT14B(b)	2S,21S	3	102	222	-40	85	-20	Y	AH-2	-
DT14BULK	2,21	3	102	222	-40	85	-20	-	AH-2	-
DT14H	2S,21S	7	102	534	-40	85	-20	-	AH-2	-
DT14HB(b)	2S,21S	7	102	534	-40	85	-20	Y	AH-2	-
DT21H	2,21	7	140	778	-40	85	-20	-	AH-2	-
DT21HB	2,21	7	140	778	-40	85	-20	Y	AH-2	-
DT36H	2,21	7	263	778	-40	85	-20	-	AH-2	-
DT36HB	2,21	7	263	778	-40	85	-20	Y	AH-2	-

DT4	2,21	1.5	22	80	-40	85	-20	-	AH-2	-
DT48G	2,21	7	365	778	-40	85	-20	-	AH-2	-
DT4B	2,21	1.5	22	80	-40	85	-20	Y	AH-2	-
DT4BULK	2,21	1.5	22	80	-40	85	-20	-	AH-2	-
DT5	2,21	1.5	40	80	-40	85	-20	-	AH-2	-
DT5B	2,21	1.5	40	80	-40	85	-20	Y	AH-2	-
DT5BULK	2,21	1.5	40	80	-40	85	-20	-	AH-2	-
DT6	2S,21S	3	50	222	-40	85	-20	-	AH-2	-
DT6B(b)	2S,21S	3	50	222	-40	85	-20	Y	AH-2	-
DT6BBULK	2,21	3	50	222	-40	85	-20	Y	AH-2	-
DT6BULK	2,21	3	50	222	-40	85	-20	-	AH-2	-
DTP11	2S,21S	3	70	222	-40	85	-20	-	AH-2	-
DTP14	2S,21S	3	102	222	-40	85	-20	-	AH-2	-
DTP6	2S,21S	3	50	222	-40	85	-20	-	AH-2	-

(b) - Type 2S nonmetallic cable ties manufactured in Black color only have been evaluated for Outdoor use (Resistance to UV)

Last Updated on 2024-05-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."