UL Product **iQ**[™]

ZODZ2.E478898 - Positioning Devices - Component

Positioning Devices - Component

See General Information for Positioning Devices - Component

L H DOTTIE CO

6131 GARFIELD AVE COMMERCE, CA 90040-3610 USA

Nonmetallic Cable Ties with Integral Push Mount or Screw Mount Devices Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm (in.)		Loop Tensile Str., N (lbf)	Mechanical Str., N(lbf)	Operating Temp., °C(°F)		Min. Install. Temp., °C(°F)	Resistant to UV Light	Material Flame Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Мах			Min	Max	_			
DTM11	11	3 (0.12)	76 (2.99)	222 (50)	222 (50)	-40 (-40)	85 (185)	0 (32)	-	V-2	-
DTM14	11	3 (0.12)	102 (4.02)	222 (50)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	V-2	-
DTM14B	11	3 (0.12)	102 (4.02)	222 (50)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	V-2	-
DTM6, DTMP6	1,11	3 (0.12)	47 (1.85)	222 (50)	222 (50)	-40 (-40)	85 (185)	0 (32)	-	V-2	-
DTM6B	1,11	3 (0.12)	47 (1.85)	222 (50)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	V-2	-

Marking: Company name, catalog or model number, the Recognized Component Mark, and, if published with the product, the product's maximum and minimum operating temperature, minimum installation temperature if below 0°C, minimum and maximum bundle diameter, loop tensile strength, type designation and/or declared mechanical strength on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2020-06-16

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

E478898

(UL)